

# LABELSTOCK

### POLYESTER/PEN BASED FILM

#### L-133

#### 0.050mm

• Thermal transfer white polyester labelstock with UV resistant adhesive



## RD-690

0.050mm

 Anti-static polyester labelstock



## L-133T

### 0.050mm

 Most economical white polyester labelstock



### 0.050mm 0.100mm

White polyester labelstock with silicone adhesive



## SP-2549

## 0.050mm

Matt silver labelstock

## RD-713B

## 0.050mm

• PEN based white printable labelstock



















## L-133

### polyester labelstock for thermal transfer printing

L-133 is a high temperature thermal transfer printable labelstock. Designed to be printed with high performance resin /resin-wax based ribbons, L-133 will withstand temperatures up to 200°C and is resistant against many solvents and processing chemicals.

#### **Application:**

- Electronic Industry: For topside of printed circuit boards and for component labelling.
- Automotive Industry
- Airmotive Industry
- General Industrial applications requiring high temperature resistance and or chemical resistance

#### **Properties:**

- thermal transfer printing
- suitable for barcode printing
- smudge resistant

#### RD-690

#### anti-static polyester film labelstock

based on polyester film coated with a synthetic resin based adhesive. The special construction of synthetic resin based adhesive prevents any static discharge during removal from interliner or from applied surface after use.

#### **Application:**

- Anti-static removable labelstock.
- Suitable for use in electronic applications where static sensitive devices and components are present.

## RD-471B

#### polyester labelstock for thermal transfer printing

#### **Application:**

- Electronic industry: for topside of printed circuit boards and for component labelling
- Automotive industry
- Aerospace industry
- Metal processing
- Freezer product labelling
- General industrial applications requiring high/low temperature resistance and/or chemical resistance

#### **Properties:**

- wide temperature range: -80°C to 155°C
- thermal transfer printable
- suitable for barcode printing
- resistant against most chemicals, solvents and oils.
- resistant against cleaning solvents and flux solutions.

### RD-713B

#### PEN labelstock for thermal transfer printing

RD-713 is a high temperature thermal transfer printable labelstock. Designed to be printed with high performance resin based ribbons, RD-713 will withstand temperatures up to 200°C and is resistant against many solvents and processing chemicals.

#### **Application:**

- Electronic Industry: For underside of printed circuit boards and in surface mount applications.
- Automotive Industry
- Airmotive Industry
- Metal processing
- General Industrial applications requiring high temperature resistance and/or chemical resistance

### **Properties:**

- thermal transfer printing
- suitable for barcode printing
- smudge resistant
- resistance against chemicals & solvents